

S8727

6W/H/LED/CFL/835/2P/BP

6W LED PL 2-PIN; 3500K; 600 Lumens; GX23 base; 50000 Average rated hours; 120 deg. beam spread; 120-277V; Type B; Ballast Bypass



Features

- Replaces 13 watt CFLs
 Ballast bypass
 Instant on to full brightness / no flickering
 Universal operating position
 Up to 70% energy saving

Suitable for use in totally enclosed, recessed luminaires. Enclosed fixture rating based on 8 hours per day of use.

S8727

	Item UPC Number		Watts	Watts Opera Frequ			escent valent	Lamp Shape	Base	Lamp C	ode
S87	S8727 045923087271		6	50/60H		13 wa	13 watt CFL		GX23	6W/H/LED/CFL/835/2P/BP	
Dimmable/Non-Dimmable			Finish MOL Inche			MOD In Inches	Initial Lu	ımens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable			Frost 5-13/1		6''	1-1/4"	600		50000	3500	Neutral White
CRI	Beam Spread Pack Packago		Type CEC Status		RoHS Compliant		UL or ETL Listed	UL Classification			
83	120	50/10	Вох			Lawful for sale in California		⁄es	Yes	cULus Classified - Damp Location Rated	
Warranty											
5 Year Limited											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051