

S8893

13T8/LED/48-850/DUAL/BP-DR 13W T8 LED; Type A + Type B; Medium bi-pin base; 5000K; 50000 Hours; 1900 Lumens; Ballast Dependant or Ballast Bypass; Single or Double Ended Wiring

Features

- LED Hybrid T8 Type A + Type B. Direct replacement or bypass
- System Performance: Ballast Compatible â€" bare lamp is 12W; Ballast Bypass â€" 13W
- Solid state LED lighting
- High efficacy
- DLC Listed
- Do not use with dimmers in by-pass mode. Check the ballast for dimming capability when using with a ballast.
- NSF Approved
- PET coated glass tube
- Protection from arcing***
- Bypass mode works wired as a single ended lamp on nonshunted sockets or as a double ended lamp on either shunted or non-shunted sockets

*** Power must be turned off prior to installing lamps. Sockets must be in good working order, not broken, cracked or electrically compromised. If arcing occurs at the lamp pin, thermal fuse may activate to avoid overheating of lamp.

May not be compatible with all ballasts.

View:

Ballast Compatibility Chart
Emergency Ballast Compatibility Chart

S8893

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base	Lamp Code	
S8893	045923088933	13	50/60Hz	Т8	Medium Bi- Pin	G13	13T8/LED/48- 850/DUAL/BP-DR	

CRI Beam Spread Deg Operating Temperature Pack CEC Status DLC ID: RoHS Compliant Listed 83 240 -20C (-4F) to a maximum of +45C (+113F) 25 Lawful for sale in California PLNHA25J4BZQ DLC Search Yes Ves UL Classification Warranty	Dimmable/Non-Dimmable		Finish	Finish MOL Ir Inches		MOD In Inches	Initial Lumens		Average Rated Hours	Kelvin Temp	Color	
Spread Deg	7 1			48"		1.00"	1	900	50000	5000	Natural Light	
UL Classification California DLC Search Warranty	CRI		Operating Temperature Pack				CEC Sta	atus DLC ID:				UL or ETL Listed
	83	240	/5			25					Yes	Yes
cl II us Listed for Type A: cl II us Classified for Type B - Damp Location Rated 5 Year Limited	UL Classification										Warranty	
5 Tear Limited	cULus Listed for Type A; cULus Classified for Type B - Damp Location Rated									5 Year Limited		

MOD In

MOL In



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051

Average Rated

Kelvin