

## S9382

6.5MR16/LED/40'/27K/120V/GU10 6.5 watt; LED MR16 LED; 2700K; 40' beam spread; GU10 base; 120 volts

## Features

- Solid State LED lighting
  High Efficacy
  Long life
  Dimmable

- UL approved for totally enclosed fixtures



S9382

| Item Numbe | Number UPC |                    | Voltage Watts Incand   |          | descent Equivalent F |      |                  | r Factor         | Lamp Shape       | Base                        |                    |
|------------|------------|--------------------|------------------------|----------|----------------------|------|------------------|------------------|------------------|-----------------------------|--------------------|
| S9382      |            | 045923093821       | 120 6.5                |          | 50\                  | )W   |                  | ).92             | MR16             | GU10                        |                    |
|            | Lamp       | ) Code             | Dimmable<br>Dimma      |          | Sugges<br>Dimme      |      | MOL In<br>Inches | MOD In<br>Inches | Initial<br>Lumen | Average<br>Rated<br>s Hours | Kelvin<br>Temp     |
| 6.5MR16/L  | -ED/40     | 0'/27K/120V/GU10   | Dimma                  | ble      | Compate dimmers S938 | for  | 2-3/16"          | 2.00"            | 500              | 25000                       | 2700               |
| Color      | CRI        | Beam Spread<br>Deg | Operating <sup>-</sup> | Гетрегаt | ture                 | Pack | : Packa          | ge Type          | RoHS C           | ompliant                    | . or ETL<br>Listed |

| Color                                | CRI | Deg | Operating Temperature                       | Pack  | Package Type | RoHS Compliant | Listed |  |  |
|--------------------------------------|-----|-----|---|-------|--------------|----------------|--------|--|--|
| Warm<br>White                        | 80  | 40  | -25C (-13F) to a maximum of<br>+45C (+113F) | 48/12 | Box          | Yes            | Yes    |  |  |
| Warranty                             |     |     |   |       |              |                |        |  |  |
| 5 Year Limited - 10 hour use per day |     |     |   |       |              |                |        |  |  |
|                                      |     |     |   |       |              |                |        |  |  |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051