



S9391

22W/LED/HID/5000K/100-277V E26
22 watt - LED HID Replacement; 5000K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
- Ballast by-pass - Direct wire only 100V - 277V
- UL approved for totally enclosed fixtures
- Damp location - IP65 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cULus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size		
Length	Width	Depth
8.5 inch	6 inch	6 inch

Optional accessory: In-line surge protector [80-929](#)

This item has been discontinued.
Possible replacement:

- [S29391](#)



S9391

Item Number	Product Line	UPC	Input Voltage	Watts	Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9391	Hi-Pro	045923093913	100 - 277	22	150W	40W	100W

Base	ANSI Base	Lamp Code		Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens
Medium	E26	22W/LED/HID/5000K/100-277V E26		Non-Dimmable	White	7-11/16"	2-3/4"	2950
Average Rated Hours	Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature		Pack	Package Type
50000	5000	Natural Light	80+	300	-20C (-4F) to a maximum of +65C (+149F)		48	Box
CEC Status	RoHS Compliant	UL or ETL Listed	Warranty	Status	Suggested Substitute			
Non-Compliant	Yes	Yes	5 Year Limited	Discontinued	This item has been discontinued. Possible replacement: <ul style="list-style-type: none"> • S29391 			



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com
 Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico
 Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717
 800.437.2826 631.243.2022 Fax 631.243.2027

