

## S9393

45W/LED/HID/5000K/100-277V/EX39 45 watt - LED HID Replacement; 5000K; Mogul extended base; 100-277 volts

## Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
  Ballast by-pass Direct wire only 100V 277V
  UL approved for totally enclosed fixtures
  Damp location IP65 rated

- For outdoor & indoor use
- DLC Listed
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- Classified under UL 1598C

## Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V

Minimum Compartment Size						
Length	Width	Depth				
17.3 inch	9.25 inch	9.25 inch				

Optional accessory: In-line surge protector 80-929

This item has been discontinued. Possible replacement:

• S29393



S9393

Item Number	Product Line	UPC	Input Voltage Watt		Incandescent Equivalent	Fluorescent Equivalent	HID Equivalent
S9393	Hi-Pro	045923093937	100 - 277	45	300W	65W	175W

Base	Base		Lamp Coo	Imp Code			Dimmable		Inches	Inche	s Lumei	ns
Mogul Extended	EX39	45\	N/LED/HID/50 277V/EX3		00-	Non-l	Dimmable	White	10-3/4"	3.69"	6000	)
Average Rate Hours		Kelvin Temp	Color	CRI		Spread Deg	Operati	ing Tempe	rature	Pack	Package T	уре
50000	į	5000	Natural Light	80+	3	300	-20C (-4F) to a maxim +65C (+149F)			12	Box	
CEC Status	DI	LC ID:	RoHS Complian	, Ē	IL or ETL isted	UL Clas	sification	Warranty	Sta	itus	Suggeste Substitut	
Lawful for sale in California	P3WZ3 PTX83 DLC S	RBS	Yes		Yes		- Damp on Rated	5 Year Limited	Discon	ntinued	<u>S29393</u>	

Dimmable/Non-



ANSI

Base

National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Lamp Code

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico

Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051

MOL In

Finish

MOD In

Initial