



# S9718

25T5/LED/46-840/BP  
25 watt T5 LED; Miniature bi-pin base; 4000K; 50000 average rated hours; 3300 lumens; 277 volts

## Features

- No ballast or external driver required
- Direct wire 277V line voltage
- All glass tube
- PETa€shatterproof coated
- NSF Approved



S9718

This item has been discontinued.  
Possible replacement:

- [S29718](#)

Item Number	UPC	Voltage	Watts	Lamp Shape	Base	ANSI Base	Lamp Code
S9718	045923097188	277	25	T5	Miniature Bi-Pin	G5	25T5/LED/46-840/BP

  

Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
Non-Dimmable	White	48"	0-5/8"	3300	50000	4000	Cool White

  

CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	230	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PX41MJDB <a href="#">DLC Search</a>	Yes	Yes

  

UL Classification	Warranty	Status	Suggested Substitute
cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>	Discontinued	<a href="#">S29718</a>



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

