



S9720

15T8/LED/48-830/BP/120-277V
 15W T8 LED; Medium bi-pin base; 3000K; 50000 Average rated hours; 1700 Lumens; Type B; Ballast Bypass; Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single ended wiring; Non-shunted socket
- All glass tube
- -20°C (-4°F) to 45°C (113°F) - ambient operating temperature
- Long life: 50,000 hours
- cULus classified - Damp location
- 5 year warranty
- DLC listed

S9720

* Install only in non-shunted lampholders

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S9720	045923097201	120-277	15	50/60Hz	25-32	T8	Medium Bi-Pin

ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	15T8/LED/48-830/BP/120-277V	Non-Dimmable	Gloss White	48"	1.00"	1700	50000

Kelvin Temp	Color	CRI	Beam Spread Deg	Pack	CEC Status	DLC ID:	RoHS Compliant
3000	Warm White	82	230	10	Lawful for sale in California	P3AEX5ZM; PP4RYCMN DLC Search	Yes

UL or ETL Listed	UL Classification	Warranty
Yes	cULus - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

