



# S9901

9T8/LED/24-835/BP 120-277V  
9 watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average  
rated hours; 1100 Lumens

## Features

- All glass tube
- Direct wire 120-277V line voltage\*
- Double ended wiring
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9901

\*Existing wiring to both sockets can remain in place

\*Will work on both shunted or non-shunted sockets

This item has been discontinued.

Possible replacement:

- [S29901](#)

Item Number	UPC	Input Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S9901	045923099014	120 - 277	9	50/60Hz	T8	Medium Bi-Pin	G13

Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp
9T8/LED/24-835/BP 120-277V	Non-Dimmable	White	24"	1.00"	1100	50000	3500

Color	CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant
Neutral White	82	210	-20C (-4F) to a maximum of +45C (+113F)	10	Lawful for sale in California	PDXTZX6T <a href="#">DLC Search</a>	Yes

UL or ETL Listed	UL Classification	Warranty	Status	Suggested Substitute



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027

