



S9906

17T8/LED/48-840/BP 120-277V
17 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens

Features

- All glass tube
- Direct wire 120-277V line voltage*
- Double ended wiring
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S9906

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

This item has been discontinued.

Possible replacement:

- [S29906](#)

| Item Number | UPC | Input Voltage | Watts | Operating Frequency | Lamp Shape | Base | ANSI Base |
|-------------|--------------|---------------|-------|---------------------|------------|---------------|-----------|
| S9906 | 045923099069 | 120 - 277 | 17 | 50/60Hz | T8 | Medium Bi-Pin | G13 |

| Lamp Code | Dimmable/Non-Dimmable | Finish | MOL In Inches | MOD In Inches | Initial Lumens | Average Rated Hours | Kelvin Temp |
|-----------------------------|-----------------------|--------|---------------|---------------|----------------|---------------------|-------------|
| 17T8/LED/48-840/BP 120-277V | Non-Dimmable | White | 48" | 1.00" | 2200 | 50000 | 4000 |

| Color | CRI | Beam Spread Deg | Operating Temperature | Pack | CEC Status | DLC ID: | RoHS Compliant |
|------------|-----|-----------------|---|------|-------------------------------|--|----------------|
| Cool White | 82 | 210 | -20C (-4F) to a maximum of +45C (+113F) | 10 | Lawful for sale in California | PC36S179 DLC Search | Yes |

| UL or ETL Listed | UL Classification | Warranty | Status | Suggested Substitute |
|------------------|-------------------|----------|--------|----------------------|
| | | | | |



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

