

S9934

11.5T8/LED/48-830/DR 11.5 watt T8 LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1700 lumens

Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Solid State LED lighting
- High efficacyDLC Listed
- Compatible with emergency ballasts*
- All glass tube

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View: Ballast Compatibility Chart **Emergency Ballast Compatibility Chart**

This item has been discontinued. Possible replacement:

• S29934

Item Number	UPC		Watts		rescent uivalent	Lamp Shape	Base	ANSI Base	Lamp	Code
S9934	045923099	9342	11.5	251	V-32W	Т8	Medium Bi- Pin	G13	11.5T8/LED	0/48-830/DR
Dimmable/No	n-Dimmable	Finish		L In hes	MOD In Inches	Initial Lum	iens ~	je Rated ours	Kelvin Temp	o Color
Non-Din	nmable	White	4	8"	1.00"	1700	50	0000	3000	Soft White
CRI _	Spread P Deg	ack Pa	ckage T	уре	CEC Status	3	DLC ID:	RoHS C	compliant	UL or ETL Listed



82	220	10	Box	Lawful for sale in California	PEM9VRFS DLC Search	Yes	Yes
UL Classification				Warranty	Status	Suggested Substitute	
cULus - Damp Location Rated			ted 5	Year Limited	Discontinued	<u>S29934</u>	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051