

## S9940

11.5T8/LED/48-840/DR-DM 11.5 watt T8 LED; Medium bi-pin base; 4000K; 50000 average rated hours; 1800 lumens

## Features

- Direct Replacement for use on Instant Start and Rapid Start ballasts with no rewiring required\*
- Solid State LED lighting
- Dimmable\*
- Compatible with emergency ballasts\*
- 25watt 32watt Fluorescent equivalency
- DLC Listed
- NSF Approved
- 5 year Limited warranty

\*May not be compatible with all rapid start, dimmable, and emergency ballasts. Ballast required

View: Ballast Compatibility Chart Dimming Ballast Compatibility Chart Emergency Ballast Compatibility Chart

This item has been discontinued. Possible replacement:

• <u>S29940</u>

Item Number	UP	С	Watts		rescent ivalent	Lamp Shape	Base		NSI ase	Lamp C	ode	
S9940	0459230	99403	11.5	25V	V-32W	Т8	Medium Pin	Bi- G	13	11.5T8/LED/48 DM		
Dimmable/Non- Dimmable		Suggested Dimmers			Finish	MOL In Inches	MOD In Inches	Initia Lumei		Average Rated Hours	Kelvin Temp	
Dimmable* Ballast Dependent		Check Ballast MFG for Dimmer Compatibility			White	48''	1.00"	1800	)	50000	4000	

S9940

Color	CRI	Beam Spread Deg	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed	
Cool White	82	220	10	Eggcrate + Sleeve	PAH6AUF2 DLC Search	Yes	Yes	
UL Classification				Warranty	Status	Suggested	Suggested Substitute	
cULus - Damp Location Rated				5 Year Limited	Discontinued	<u>S29</u>	<u>S29940</u>	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com

Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051