



S9977

15T8/LED/48-840/DR
15 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens

Features

- Direct Replacement - for use on Instant Start and Rapid Start ballasts with no rewiring required*
- Ballast required
- Solid State LED lighting
- High efficacy
- DLC Listed
- Compatible with emergency ballasts*
- All glass tube



S9977

*May not be compatible with all rapid start and emergency ballasts.

Ballast required

View:

[Ballast Compatibility Chart](#)

[Emergency Ballast Compatibility Chart](#)

This item has been discontinued.

Possible replacement:

- [S29977](#)

Item Number	UPC	Watts	Fluorescent Equivalent	Lamp Shape	Base	ANSI Base	Lamp Code
S9977	045923099779	15	25W-32W	T8	Medium Bi-Pin	G13	15T8/LED/48-840/DR
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color

Non-Dimmable	White	48"	1.00"	2200	50000	4000	Cool White
CRI	Beam Spread Deg	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
82	220	10	Box	Lawful for sale in California	P94TYM3A DLC Search	Yes	Yes
UL Classification		Warranty		Status		Suggested Substitute	
cULus - Damp Location Rated		5 Year Limited		Discontinued		S29977	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

